

SOLARMAN WIFI PLUG



- Easy plug-and-play installation for quick and convenient setup
- Preferred monitoring solution for residential use

Model	LSW-5
Connection	TTL
Standards	802.11b: +17 dBm±1.5dBm(@11Mbps) 802.11g: +15 dBm±1.5dBm (@54Mbps) 802.11n: +14 dBm±1.5dBm (@HT20, MCS7)
Transmission Maximum Distance	100m Unobstructed environment
Setting	APP / WEB
Input	
Input Voltage	DC 5V
Static Power Consumption	<1.6W
General	
Operating Temperature	-30°C~70°C
Humidity	0%~100% relative humidity, no condensation
IP Rating	IP65
Dimension (L*W*H)	79mm*34mm*122.8mm
Certification	
Safety	ANATEL/CSIP/CE/RCM

LAN COMMUNICATION MODULE PV LAN-R



- Easy plug-and-play installation for quick and convenient setup
- Mobile internet monitoring, ideal for rural and remote areas

Model	PV LAN-R
Connection	TTL
Standards	IEEE 802.3
Transmission Maximum Distance	100m CAT5
Setting	APP
Input	
Input Voltage	DC 5V
Static Power Consumption	<1.6W
General	
Operating Temperature	-25°C~60°C
Humidity	0%~100% relative humidity, no condensation
IP Rating	IP65
Dimension (L*W*H)	71mm*41mm*117mm
Certification	
Safety	FCC, CE-RED, SRRC