Safety Data Sheet Ver 1.0

Safety Data Sheet

Product Names

PrimeX-LV PV 5KBA-L / PV 10KBA-L

Section 1 – Identification: product identifier and chemical identity

Name of Sample		PV 5KBA-L, PV 10KBA-L
Manufacturing country		China
Rated DC Power		3.07/6.14 kW
Nominal Battery	Capacity	5.12/10.24kWh
Rated Voltage		51.2 V
Working Voltage	Range	44.8-58.4 V
Available SOC Range		0% ~ 100% 90%DOD is Recommended
Manuafacture	Name	PRIMEVOLT NEW ENERGY AUSTRALIA PTY LTD
	Address	Suite 1, 237 Main Street, Osborne Park WA 6017, Australia
	Telephone	03 8618 9028 ; 1800936168
	Email	Info@primevolt.com.au
		service@primevolt.com.au
	Website	https://primevolt.com.au/
Importer	Name	PRIMEVOLT NEW ENERGY
		AUSTRALIA PTY LTD
	Address	Suite 1, 237 Main Street, Osborne
		Park WA 6017, Australia
	Telephone	03 8618 9028 ; 1800936168
	Email	Info@primevolt.com.au
		service@primevolt.com.au

Section 2- Hazards Identification

Classification of Danger See section 14.

Primary Route(s) of Exposure Eye, skin contact, ingestion.

Health Hazard

The batteries are not hazardous when used according to the instructions of manufacturer under normal conditions. In case of abuse, there's Hazard of rupture, fire, heat, leakage of internal components, which could cause casualty loss. Abuses including but not limited to the following cases: charged for long time, short circuited, put into fire, whacked with hard object, punctured with acute object, crushed, and broken.

Section 3 - Composition/Information on Ingredients

Chemical Name	Concentration or concentration ranges	CAS Number
Iron Lithium Phosphate	15~40	15365-14-7
(LiFePO4)		
Graphite	7~25	7782-42-5
Hexafluoropropylene-	3~15	9011-17-0
vinylidene fluoride Copolymer		
Lithium Hexafluorophosphate	0~5	21324-40-3
Acetylene Black	0~2	1333-86-4
Diethyl Carbonate	0~15	105-58-8
Dimethyl Carbonate	0~15	616-38-6
Ethyl Methyl Carbonate	0~15	623-53-0
Propylene Carbonate	0~15	108-32-7
Ethylene Carbonate	0~15	96-49-1

Labelling according to EC directives.

No symbol and Hazard phrase are required.

Note: CAS number is Chemical Abstract Service Registry Number.

N/A = Not applicable.

Section 4 - First Aid Measures

	Flush eyes with plenty of water for at least 15
Eye	minutes, occasionally lifting the upper and
	lower eyelids. Get medical aid.
	Remove contaminated clothes and rinse skin
Skin	with plenty of water or shower for 15 minutes.
	Get medical aid.
Inhalation	Remove from exposure and move to fresh air
Imalation	immediately. Use oxygen if available.
	Give at least 2 glasses of milk or water. Induce
Ingestion	vomiting unless patient is unconscious. Call a
	physician.

Section 5 - Fire Fighting Measures

Characteristics of Hazard	Dusts at sufficient concentrations can form explosive mixtures with air. Combustion generates toxic fumes.
	-
Hazard Combustion Products	Carbon dioxide.
Fire-extingushing Methods and Extinguishing	For small fires, use water spray, dry chemical,
Media	carbon dioxide or chemical foam.
Attention in Fire-extinguishing	Wear self-contained breathing apparatus in pressure-demand, MSHA/ NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Personal Precautions, protective equipment, and emergency procedures	In case of rupture. Attention! Corrosive material. Avoid contact with skin, eyes and clothing. Ensure adequate ventilation. Use personal protective equipment as required. Evacuate personnel to safe areas. Keep people away from and upwind of spill/ leak. Refer to protective measures listed in Sections 7 and 8.
Environmental Precautions	Prevent product from contaminating soil and from entering sewers or waterways.
Methods and materials for Containment	Stop the leak if safe to do so. Contain the spilled liquid with dry sand or earth. Clean up spills immediately.
Methods and Materials for cleaning up	Absorb spilled material with an inert absorbent (dry sand or earth). Scoop contaminated absorbent into an acceptable waste container. Collect all contaminated absorbent and dispose of according to directions in Section 13. Scrub the area with detergent and water; collect all contaminated wash water for proper disposal.

Section 7 - Handling and Storage

	The battery may explode or cause burns, if
Handling	disassembled, crushed or exposed to fire or
Tranding	high temperatures. Do not short or install with
	incorrect polarity.
	Store in a cool, dry, well-ventilated area away
Storage	from incompatible substances. Store locked
	up. Keep out of the reach of children.
	In case of rupture. Handle in accordance with
Other Precautions	good industrial hygiene and safety practice.
Other Precautions	Avoid contact with skin, eyes or clothing. Use
	personal protection equipment.

Section 8 - Exposure Controls/Personal Protection

	Use adequate ventilation to keep airborne concentrations low. If used under conditions
Engineering Centrale	
Engineering Controls	that generate particulates, the ACGIH TLV-
	TWA of 3mg/ m ³ respirable fraction (10mg/m ³)
	total) should be observed.
	Eye and Face Protection: None required for
	consumer use. If there is a Hazard of contact:
	Tight sealing safety goggles. Face protection
	shield. Skin and Body Protection: None
	required for consumer use. If there is a Hazard
Personal Protective Equipment	of contact: Wear protective gloves and
	protective clothing. Respiratory Protection: No
	protective equipment is needed under normal
	use conditions. If exposure limits are
	exceeded or irritation is experienced,
	ventilation and evacuation may be required.

Section 9 - Physical and Chemical Properties

Physical State	Appearance: Prismatic
	Colour: Wihte
	Odour: If leaking, smells of medical ether.

Change in condition

pH	Not applicable as supplied.
Flash Point	Not applicable unless individual components
	exposed.
Flamibility	Not applicable unless individual components
	exposed.
Relative density	Not applicable unless individual components
	exposed.
Solubility (water)	Not applicable unless individual components
	exposed.
Solubility (other)	Not applicable unless individual components
	exposed.

Section 10 - Stability and Reactivity

Chemical Stability	Stable under recommended storage
Chemical Stability	conditions.
Possibility of Hazardous Reactions	None under normal processing.
Conditions to Avoid	Exposure to air or moisture over prolonged
Conditions to Avoid	periods.
Incompatibile materials	Acids, Oxidizing agents, Bases.
Hazardous Decomposition Products	Carbon oxides.

Section 11 - Toxicological Information

Irritation	In the event of exposure to internal contents, vapour fumes may be very irritating to the eyes and skin.
Sensitisation	Not Available.
Reproductive Toxicity	Not Available.
Toxicologically Synergistic Materials	Not Available.

Section 12 - Ecological Information

	Do not allow undiluted product or large
General Note:	quantities of it to reach ground water, water
	course or sewage system.
Anticipated behaviour of a chemical product	
in environment/possible environmental	Not Available.
impact/ ecotoxicity	

Section 13 - Disposal Considerations

Waste Treatment	Recycle or dispose of in accordance with government, state & local regulations.
Attention for Waste Treatment	Deserted batteries shouldn't be treated as
	ordinary trash. Shouldn't be thrown into fire or
	placed in high temperature. Shouldn't be

dissected, pierced, crushed or treated similarly. Best disposal method is recycling.

Section 14 - Transport Information

UN number	3480
Proper shipping name	Lithium ion batteries (limited to a maximum of 40% SoC)
Class or division	9
Label(s) / Placard Required	Miscellaneous Lithium battery
Special precautions which a user needs to be aware of, or needs to comply with, in connection	
with transport or conveyance either within or outside their premises.	
ICAO / IATA:	Can be shipped by air in accordance with International Civil Aviation Organization
	(ICAO), TI or International Air Transport Association (IATA), DGR Packing Instructions (PI) 965 Section IB appropriate of IATA DGR 60th (2019 Edition) for transportation.
IMDG CODE:	The batteries are not restricted to IMDG Code 2018 Edition (Amdt 39-18) according to special provision 188.
DOT:	Other requirements for the US Department of Transportation (DOT) Subchapter C, Hazardous Materials Regulations if shipped in compliance with 49 CFR 173.185.
ADR / ADN:	The batteries are not subject to the provisions of United Nations Economic Commission for Europe (UNECE) ADR/ADN if they meet the requirements of special provision 188 of Chapter 3.3. Applicable as from 1 January 2019.

In addition, to be permitted in transport each lithium cell and battery types must have passed the applicable tests set out in Subsection 38.3 of the UN Manual of Tests and Criteria.

Section 15 - Regulatory Information

Dangerous Goods Regulations

Recommendations on the Transport of Dangerous Goods-Model Regulations (20th revised edition)

Recommendations on the Transport of Dangerous Goods-Manual of Tests and Criteria International Air Transport Association (IATA)

International Maritime Dangerous Goods (IMDG Code 2018 Edition Amdt 39-18)

Technical Instructions for the Safe Transport of Dangerous Goods

Classification and code of dangerous goods (GB 6944-2012)

2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Toxic Substance Control Act (TSCA)

Code of Federal Regulations

In accordance with all Federal, State and local laws

Section 16 - Additional Information

Sample photos



PV 5KBA-L PV 10KBA-L

To the best of our knowledge, the information contained herein is accurate. However, neither the above named supplier nor any of its subsidiaries assumes any liability whatsoever for the accuracy or completeness of the information contained herein. Final determination of suitability of any material is the sole responsibility of the user. All materials may present unknown hazards and should be used with caution. Although certain hazards are described herein, we cannot guarantee that these are the only hazards that exist.

The data/information contained herein has been reviewed and approved for general release on the basis that this document contains no export controlled information.